



- NOTES: 1. MATERIAL:
 1-1 Housing : Engineering plastic , LCP with G.F reinforced , black per UL 94V-0 rate.
 1-2 Terminal : Phosphor Bronze , per JIS 5210 , 0.2t
 1-3 Metal cover : Stainless steel sheet SUS304 0.2t.
2. PLATING:
 Solder zone: 2.54 μ m (100 μ ") matte Tin 1.27 μ m (50 μ ") min. Nickel underplating over all.
3. RoHS compliant products.
4. OPERATING TEMPERATURE: -40°C~+85°C

TOLERANCE: ±0.10
 RECOMMENDED P.C. BOARD LAYOUT



GENERAL TOLERANCE		KINGCONN	皇海科技股份有限公司
X± 0.50	X*± 5 °		
.X± 0.30	.X*± 2 °		
.XX± 0.20	.XX*± 1 °	名稱(TITLE) CFAST HOST CONNECTOR NON-PUSH TYPE II,8.35H(缺口型)	
單位(UNIT)	料號(PART NO.)	圖號(DWG NO.)	
mm	7CFST-CA-0013	7CFST-CA-0013-A	
審核(APPROVAL)	核對(CHECKED)	製圖(DRAWN)	比例 SCALE 1:1 張數 SHEET 1 / 1 更改 REV A